



Notes:

- Open-cell Polyurethane foam core Nickel-plated copper nylon ripstop fabric For more detailed specs, see Orbel product catalog





Н	W		
0.040	0.150		
0.040	0.200		
0.050	0.140		
0.050	0.187		
0.050	0.250		
0.060	0.150		
0.060	0.250		
0.070	0.135		
0.070	0.180		
0.080	0.080		
0.080	0.157		
0.080	0.394		
0.090	0.090		
0.090	0.150		
0.100	0.300		
0.110	0.180		
0.120	0.150		

ENGINEERED SOLUTIONS

CAGE CODE: 57DU2

01

SHEET 1 OF 1

SIZE DWG NO.

A D-SHAPED

RoHS Compliant	DIMENSIONS ARE IN INCHES [MILLIMETERS] TOLERANCES: FRACTIONAL± ANGULAR: MACH± 3 Degrees TWO PLACE DECIMAL ± .030 [.762] THEFE PLACE DECIMAL ± .020 [.508]		NAME	DATE
THIRD FRACTIONAL± ANGLE ANGLE ANGULAR: MACH± 3 Degrees		DRAWN	TNC	8/9/2019
		CHECKED		
		ENG APPR.		
	MFG APPR.			
PROPRIETARY AND CONFIDENTIAL		Q.A.		
IHE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ORBEL CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF	FINISH:	COMMENTS:		
ODDEL CODDODATION IS DECLIBITED	WEIGHT 0 (00 - 117 007 - 1	1		

ULTRAFLEX™ CONDUCTIVE FOAM

Mechanical Properties

- Material Specification: Flame-retardant nickel-plated copper polyurethane foam protected between two layers of conductive polyester fabric
- Adhesive: 0.002"-thick nickel-filled conductive acrylic tape
- Configurations: Sheets, strips, or custom die-cuts
- Deflection Range: 30%-75% deflection
- Compression Force: 2.1 pounds per square inch at 30% deflection
- Temperature Range: -40°F to 158°F (-40°C to 70°C)
- Flammability: UL94HB

Electrical Properties

- Surface Resistivity: <0.02 ohms per square inch</p>
- Z Resistivity: <0.01 ohms</p>
- Shielding Effectiveness: >60dB attenuation 30MHz to 3GHz

Environmental Properties

 Shelf Life: 2 years if stored in a temperatureand humidity-controlled environment

HOW TO ORDER METALIZED FABRIC GASKETS

Sample Part Number: 125R250-024000N

