



PART NUMBER	DESCRIPTION
L-0900CC1375-0190XC	COVER
L-0900SA1375-0190XF	FRAME



DETAIL A  
SCALE 5 : 1

RoHS Compliant		NAME	DATE
<b>THIRD ANGLE PROJECTION</b> 	DIMENSIONS ARE IN INCHES [MILLIMETERS]		DRAWN
	TOLERANCES:		RAM
	FRACTIONAL ±		08/26/2020
	ANGULAR: MACH ± 3 Degrees		CHECKED
	TWO PLACE DECIMAL ± .015 [.381]		ENG APPR.
THREE PLACE DECIMAL ± .010 [.254]		MFG APPR.	
MATERIAL:		Q.A.	
.010" [.254] NICKEL SILVER, 1/2 HARD		COMMENTS:	
FINISH:			
WEIGHT: 0.095oz [2.686g]			



SIZE	DWG NO.	REV.
A	L-0900CC1375-0190XC	01
SCALE: 1:1	CAGE CODE: 57DU2	SHEET 1 OF 1

# HOW TO ORDER BOARD LEVEL SHIELDING

The chart below is an easy-to-use reference on how Orbel BLS part numbers are created and used to order standard and custom board level shielding. Custom configurations that fall outside of our standard shield styles are also available.

## Sample Part Number (Snap-Shield Bullzeye™): B-0750TB1125-0250XF - TPS



# STANDARD FEATURES

## PIN OPTIONS



Alignment Pin



Through-Hole Pin



Through-Hole Pin with Standoff



Castellation Edge



Straight Edge, No Pin

## CORNER OPTIONS



Tight Corner



Louvered Corner



Welded Corner

## ADDITIONAL OPTIONS



Trace Notch



Pick Target



Ventilation Holes



Logo or Part Number Marking

# PERFORMANCE SPECS

### Material Options

- Nickel Silver
- TPS: Tin-Plated Steel
- TPB: Tin-Plated Brass
- TPC: Tin-Plated Copper

### Co-Planarity

- Smaller Shields: 0.004"
- Larger Shields: 0.008"

### Material Thicknesses

- 0.010" (Standard)
- 0.008"
- 0.012"
- 0.015"

### RoHS-Compliant

- Yes

### Shielding Effectiveness

- Up to 60dB

*Other material options include beryllium copper, phosphorus bronze, and stainless steel. Additional plating finishes available upon request.*

*All technical data presented herein is accurate to the best of our knowledge based on Orbel's most up-to-date testing information and material specs. This information is not presented as a warranty or guarantee and is not intended to be all-inclusive as to conditions of use.*